

ANT-2010 HDMI & DVI Input H.264 HD 1080P60 Set Top Box Video Encoder
Product Code: ANT-2010



Key Features

- 1920 x 1800 P60 Max Resolution
- H.264 Simple Encoder
- HDMI Inputs & Outputs
- HTTP, RTSP, RTMP and MPEG-TS over UDP Streaming Supported
- Unicast and Multicast MPEG-TS

Product Overview

ANT-2010 dual Stream HDMI & DVI Input H.264 HD 1080P60 Video Encoder, capable of up to a maximum 1920 x 1080 at 60 frames per sec encode with dual streaming using an IP LAN ethernet connection. Ideal for encoding the output of a set top box for streaming to other locations or recording.

The inputs are HDMI & DVI. Inputs and outputs are provided to allow for signal bypassing or looping.

Multiple streaming formats are supported such as HTTP, RTSP, RTMP and MPEG-TS over UDP.

The encoder is powered via 12V.

AAC and MP3 audio is supported with embedded audio in HDMI.

There is no RS232/485/422 2 way serial data communication, motion detection, sensor and alarm I/O, please see the ANT-35000A or ANT-35000H for this feature.

This encoder is NOT fully ONVIF compliant though does offer ONVIF discovery of profiles only

A few of the applications are:

- ✓ Encode a PC screen and send to a VMS for monitoring, recording and litigation purposes.
- ✓ Encode video from a piece of medical equipment and send to remote consultant to oversee the procedure.
- ✓ Encode the output of a set top box for viewing remotely elsewhere

This product is not limited to the markets and applications described.
Please download or full application catalogue [here](#).

ANT-2010 HDMI & DVI Input H.264 HD 1080P60 Set Top Box Video Encoder
 Product Code: ANT-2010

Technical Specification

		ANT-2010
System	Mode	Encoder
System	Standards	ONVIF Discovery, RTSP, RTMP,HTTP, MPEG-TS
System	Latency	>150mS (system dependant)
Video	Compression	H.264
Video	Profile	Base, Main or High
Video	Frame Rate	1-60 fps
Video	Bit Rate	16-12 mbps
Video	Mode	GOP
Video	Bit Rate Control	CBR, VBR
Video	Min Resolution	320 x 180
Video	Max Resolution	1920 x 1080
Video	Number of Streams	Primary 1 x H.264 / Secondary 1 x H.264
Video	Inputs	1 x HDMI (DVI)
Video	Input Combinations	Any 1 Input
Video	Outputs	1 x HDMI (DVI)
Video	Output Combinations	Any 1 Output
Video	On Screen Display	English
Audio	Mode	Simplex Stereo
Audio	Compression	G.711 + AAC + MP3
Audio	Sample Rate	G711 = 8Khz , AAC= 32/44.1kHz MP3 = 32/44.1kHz
Audio	Bit Rate	G711=64kbps, AAC= 24-256kb/s MP3 = 24-256kb/s
Audio	Streaming	1 Way Stereo
Audio	Inputs	Analogue Stereo Jack (1vpp) or Embedded Audio
Audio	Outputs	Embedded Audio
Network	Interface	10-100 Ethernet RJ45
Network	Protocols	IPv4, TCP, UDP, IGMP(Multicast), DHCP,HTTP, RTP,RTSP, DNS
Network	Security	Password Protection
Network	Configuration	SDK, WEB
Data	Type	N/A
Data	Interface	N/A
Data	Protocol	N/A
Data	Alarm	N/A
Data	Sensor	N/A
Event	Sources	N/A
Event	Actions	N/A
Power	Supply	12v
Power	Adapter input volts	AC 110-240v
Power	Adapter Output Voltage	12v DC
Power	Consumption	9.6w
Recording	Edge Storage	N/A
Temperature	Operating Range	0 + 50C
Physical	Dimensions	147 x 100 x 40mm
Physical	Weight	295g
Physical	Housing	Black Aluminum
General	Certifications	CE , FCC, RoHS
General	Software	N/A
General	Warranty	12 Months
General	Remote	N/A
General	Reset	Web or external
Control & Set Up	Set Up	Web Interface API Document
	Control	API
	Upgrade	Firmware Upgrade
In the Box	Contents	Encoder , 12v Power Supply & Lead, HDMI, & Fixing Kit
	Power Cable/adapter	1 of either UK/US/EU/China/Aus
General	Certifications	CE , FCC, RoHS
	Software	IP Finder + VMS
	Warranty	12 Months
	Remote	N/A
	Reset	Web or external
Control & Set Up	Set Up	Web Interface API Document
	Control	Web or ONVIF
	Upgrade	Firmware Upgrade
In the Box	Contents	Camera , 12v Power Supply
	Power Cable/adapter	UK/US/EU/China/Aus